

PRODUCT-DETAILS

# CP1-10G-10

## PUSHBUTTON CP1-10G-10



### General Information

|                       |  |
|-----------------------|--|
| Extended Product Type | CP1-10G-10   |
| Product ID            | 1SFA619100R1012  |
| EAN                   | 7320500550373  |
| Catalog Description   | PUSHBUTTON CP1-10G-10  |
| Long Description      | Compact Pushbutton - Momentary - Flush - Green - Non-illuminated - Black plastic - 1NO |

### Ordering

|                        |            |
|------------------------|------------|
| Minimum Order Quantity | 10 piece   |
| Customs Tariff Number  | 8536501999 |

### Popular Downloads

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SFC151007C02__ |
| Instructions and Manuals          | 1SFC151011M0201 |

### Dimensions

|                    |        |
|--------------------|--------|
| Product Net Width  | 0.03 m |
| Product Net Height | 0.03 m |

|                            |          |
|----------------------------|----------|
| Product Net Depth / Length | 0.055 m  |
| Product Net Weight         | 0.018 kg |

## Technical

|   |   |
|---|---|
| Ambient Air Temperature                             | Operation -25 ... +70 °C<br>Storage -40 ... +85 °C        |
| Color   | Green   |
| Actuator Type                                       | Flush   |
| Bezel Material                                      | Black Plastic   |
| Illumination  | Non-illuminated   |
| Function  | Momentary   |
| Number of Auxiliary Contacts NC                     | 0   |
| Number of Auxiliary Contacts NO                     | 1   |
| Degree of Protection                                | Front IP66<br>Front IP67<br>Front IP69K<br>Terminals IP20 |
| Enclosure Type NEMA                                 | Type1<br>Type12<br>Type13<br>Type3R<br>Type4<br>Type4X    |
| Pollution Degree                                    | 3   |
| Rated Insulation Voltage (U <sub>i</sub> )          | 300 V   |
| Rated Impulse Withstand Voltage (U <sub>imp</sub> ) | 6 kV  |
| Rated Frequency (f)                                 | 50 / 60 Hz  |
| Rated Operational Voltage                           | Maximum 300 V AC/DC                                       |
| Rated Operational Current DC-13 (I <sub>e</sub> )   | (24 V) 0.3 A<br>(125 V) 0.2 A                             |
| Rated Operational Current AC-15 (I <sub>e</sub> )   | (240 V) 1 A   |
| Power Loss  | Maximum 2.5 W   |
| Mechanical Durability                               | 0.5 million   |
| Terminal Type                                       | Screw Terminals   |
| Tightening Torque                                   | 0.8 N·m   |
| Wire Stripping Length                               | 6 mm  |

## Environmental

|                  |  |
|------------------|--|
| RoHS Status      | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| RoHS Date        | 0626 5   |
| RoHS Information | 2CMT2015-005451  |
| WEEE Category    | 5. Small Equipment (No External Dimension More Than 50 cm)             |
| WEEE B2C / B2B   | Business To Business   |

## Certificates and Declarations (Document Number)

|                   |                     |
|-------------------|---------------------|
| CB Certificate    | CQC_CN_CN50749      |
| CCC Certificate   | 2003010305054693_   |
| CQC Certificate   | CQC2003010305054693 |
| cURus Certificate | UL_E496500-20171020 |

|                                 |                         |
|---------------------------------|-------------------------|
| Declaration of Conformity - CCC | 2020980305001187        |
| Declaration of Conformity - CE  | 2CMT2015-005451         |
| DNV GL Certificate              | 9AKK107046A3749         |
| EAC Certificate                 | RU C-CN.ME77.B.00587/20 |
| Environmental Information       | 1SAC200027H0002         |
| Instructions and Manuals        | 1SFC151011M0201         |
| RoHS Information                | 2CMT2015-005451         |

## Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | bag 10 piece  |
| Package Level 1 Width          | 0.125 m       |
| Package Level 1 Depth / Length | 0.235 m       |
| Package Level 1 Height         | 0.05 m        |
| Package Level 1 Gross Weight   | 0.184 kg      |
| Package Level 1 EAN            | 7320500240724 |

## Classifications

|                            |  |
|----------------------------|--|
| Object Classification Code | S  |
| ETIM 4                     | EC002024 - Accessories for control circuit devices |
| ETIM 5                     | EC001028 - Push button, complete                   |
| ETIM 6                     | EC001028 - Push button, complete                   |
| ETIM 7                     | EC001028 - Push button, complete                   |
| eClass                     | V11.0 : 27371228                                   |
| UNSPSC                     | 39121500   |
| E-Number (Finland)         | 2312703  |
| E-Number (Norway)          | 4373394  |
| E-Number (Sweden)          | 3705385  |

## Categories

Low Voltage Products and Systems → Control Products → Pilot Devices → Compact Range

