

PRODUCT-DETAILS

CL2-502R

Compact Pilot Light Red LED 24V AC/DC



General Information

| | |
|-----------------------|--|
| Extended Product Type | CL2-502R |
| Product ID | 1SFA619403R5021 |
| EAN | 7320500556085 |
| Catalog Description | Compact Pilot Light Red LED 24V AC/DC |
| Long Description | Compact Pilot Light - Pilot light head - Red - Illuminated - Lamptype: LED 24V AC/DC |

Ordering

| | |
|------------------------|------------|
| Minimum Order Quantity | 10 piece |
| Customs Tariff Number | 8536619090 |

Popular Downloads

| | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SFC151007C02_ |
| Instructions and Manuals | 1SFC151011M0201 |

Dimensions

| | |
|---------------------|---------|
| Product Net Width | 0.03 m |
| Product Net Height | 0.03 m |
| Product Net Depth / | 0.052 m |

Length

| | |
|--------------------|----------|
| Product Net Weight | 0.018 kg |
|--------------------|----------|

Technical

| | |
|---------------------------|---|
| Ambient Air Temperature | Operation -25 ... +70 °C Storage -40 ... +85 °C |
| Color | Red |
| Actuator Type | Pilot light head |
| Illumination | Illuminated |
| Lamp Type | 24V AC / DC, integrated LED |
| Degree of Protection | Front IP66 Front IP67 Front IP69K Terminals IP20 |
| Enclosure Type NEMA | Type1 Type12 Type13 Type3R Type4 Type4X |
| Pollution Degree | 3 |
| Rated Frequency (f) | Supply Circuit 50 / 60 Hz |
| Rated Operational Voltage | Supply Circuit 24 V AC/DC |
| Terminal Type | Screw Terminals |
| Tightening Torque | 0.9 N·m |
| Wire Stripping Length | 8 mm |

Environmental

| | |
|------------------|--|
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| RoHS Information | 2CMT2015-005451 |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B | Business To Business |

Certificates and Declarations (Document Number)

| | |
|--------------------------------|-----------------------------|
| CB Certificate | CQC_CN_CN50749 |
| cULus Certificate | UL_E496500-20171020 |
| cURus Certificate | UL_E496500-20171020 |
| Declaration of Conformity - CE | 2CMT2015-005451 |
| DNV GL Certificate | 9AKK107046A3749 |
| EAC Certificate | EAC-RU C-CN.ME77.B.00690_20 |
| Environmental Information | 1SAC200026H0002 |
| Instructions and Manuals | 1SFC151011M0201 |
| RoHS Information | 2CMT2015-005451 |

Container Information

| | |
|--------------------------------|--------------|
| Package Level 1 Units | bag 10 piece |
| Package Level 1 Width | 0.125 m |
| Package Level 1 Depth / Length | 0.235 m |
| Package Level 1 Height | 0.05 m |
| Package Level 1 Gross | 0.184 kg |

Weight

Package Level 1 EAN

7320500475737

Classifications

| | |
|--------------------|-------------------------------------|
| ETIM 5 | EC000272 - Indicator light complete |
| ETIM 6 | EC000272 - Indicator light complete |
| ETIM 7 | EC000272 - Indicator light complete |
| eClass | V11.0 : 27371223 |
| UNSPSC | 39121500 |
| E-Number (Finland) | 2313507 |
| E-Number (Norway) | 4373505 |
| E-Number (Sweden) | 3705751 |

Categories

Low Voltage Products and Systems → Control Products → Pilot Devices → Compact Range → CL

