

## APPLIANCE AND FIXTURE WIRE

**High Temperature Lead Wire**  
**SF-2**  
**200°C - 600 Volt - UL Listed**



| CONSTRUCTION |   |
|--------------|---|
| Conductor    | • Stranded tinned copper                          |
| Insulation   | • Silicone rubber                                 |
| Jacket       | • Fiberglass braid with a high temperature finish |

### Applications:

- Suitable for UV, ozone, and moisture exposure
- Suitable for applications to -40°C

### Standards:

- UL Listed

| Part #    | AWG | Stranding | Insulation Thickness | Nom. O.D. | Lbs./M' |
|-----------|-----|-----------|----------------------|-----------|---------|
| C71801-XX | 18  | 7         | .030"                | .120"     | 12.5    |
| C71601-XX | 16  | 7         | .030"                | .130"     | 16      |
| C71401-XX | 14  | 7         | .030"                | .145"     | 22      |
| C71201-XX | 12  | 19        | .030"                | .165"     | 32      |
| C71001-XX | 10  | 19        | .045"                | .220"     | 54      |

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances.

Insert the color number in the -XX location:

- 01 = Black
- 02 = White
- 03 = Red
- 04 = Green
- 05 = Blue
- 06 = Gray
- 07 = Orange
- 08 = Yellow
- 09 = Purple
- 10 = Brown