

## Timer module, 100-130VAC, 5-100s, off-delayed

**Part no. DILM32-XTED11-100(RAC130)**  
**104947**

Product name	Eaton Moeller® series DILM timer module
Part no.	DILM32-XTED11-100(RAC130)
EAN	4015081048052
Product Length/Depth	86 millimetre
Product height	38 millimetre
Product width	45 millimetre
Product weight	0.073 kilogram
Certifications	UL File No.: E29184 UL 508 IEC/EN 60947-4-1 VDE 0660 CE CSA Class No.: 3211-03 DIN EN 61812 CSA CSA-C22.2 No. 14-05 UL Category Control No.: NKCR UL IEC/EN 60947 CSA File No.: 012528
Product Tradename	DILM
Product Type	Accessory
Product Sub Type	Timer module
Catalog Notes	Cannot be combined with top mounting auxiliary contacts
Fitted with:	Suppressor circuits
Switch function type	Time-delay dropped out
Operating mode	Electronic
Degree of protection	IP20
Delay time	200 ms, Off-delayed 50 ms, On-delayed
Lifespan, mechanical	3,000,000 Operations (DC operated) 3,000,000 Operations (AC operated)
Operating frequency	3600 Operations/h 360 mechanical Operations/h
Overvoltage category	III
Pollution degree	3
Product category	Accessories
Protection	Finger and back-of-hand proof, Protection against direct contact when actuated from front
Rated impulse withstand voltage (Uimp)	4000 V AC
Recovery time	70 ms (after 100 % time delay)
Repetition accuracy	< 5 % (deviation)
Mounting position	As required (except suspended)
Shock resistance	6 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms 6 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms
Ambient operating temperature - min	-25 °F
Ambient operating temperature - max	60 °F
Ambient operating temperature (enclosed) - min	25 °F
Ambient operating temperature (enclosed) - max	40 °F
Ambient storage temperature - min	40 °F

Ambient storage temperature - max		80 °F
Climatic proofing		Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Terminal capacity (flexible with ferrule)		2 x (0.75 - 1.5) mm <sup>2</sup> 1 x (0.75 - 1.5) mm <sup>2</sup>
Terminal capacity (solid)		1 x (0.75 - 2.5) mm <sup>2</sup> 2 x (0.75 - 1.5) mm <sup>2</sup>
Terminal capacity (solid/stranded AWG)		18 - 14
Screw size		M3.5, Terminal screw, Control circuit cables
Screwdriver size		0.8 x 5.5/1 x 6 mm, Terminal screw, Standard screwdriver 2, Terminal screw, Pozidriv screwdriver
Rated operational current (Ie)		0.1 A at 220 V, DC-13 L/R - 300 ms (with 1 contact in series) 0.2 A at 110 V, DC-13 L/R - 300 ms (with 1 contact in series) 0.1 A at 220 V, DC-13 L/R - 50 ms (with 1 contact in series) 1 A at 24 V, DC-13 L/R - 50 ms (with 1 contact in series) 0.2 A at 110 V, DC-13 L/R - 50 ms (with 1 contact in series) 0.2 A at 60 V, DC-13 L/R - 50 ms (with 1 contact in series) 1 A at 24 V, DC-13 L/R - 300 ms (with 1 contact in series) 0.2 A at 60 V, DC-13 L/R - 300 ms (with 1 contact in series) 3 A at AC-15, 220 V 230 V 240 V
Short-circuit current rating (basic rating)		125 A, max. CB, SCCR (UL/CSA) 5 kA, SCCR (UL/CSA) 125 A, max. Fuse, SCCR (UL/CSA)
Short-circuit current rating (high fault at 480 V)		125/70 A, Class J, max. Fuse, SCCR (UL/CSA) 10/65 kA, CB, SCCR (UL/CSA) 50/32 A, max. CB, SCCR (UL/CSA) 10/100 kA, Fuse, SCCR (UL/CSA)
Short-circuit current rating (high fault at 600 V)		10/100 kA, Fuse, SCCR (UL/CSA) 125/125 A, Class J, max. Fuse, SCCR (UL/CSA) 50/32 A, max. CB, SCCR (UL/CSA) 10/22 kA, CB, SCCR (UL/CSA)
Short-circuit protection rating		Max. 4 A gG/gL, fuse, Without welding, Auxiliary and control circuits
Switching capacity (auxiliary contacts, general use)		5 A, 240 V AC, (UL/CSA) 5 A, 24 V DC, (UL/CSA)
Switching capacity (auxiliary contacts, pilot duty)		R300, DC operated (UL/CSA) B300, AC operated (UL/CSA)
Duty factor		100 %
Pick-up voltage		0.7 - 1.2 V DC x Uc 0.85 - 1.1 V AC x Uc
Power consumption, sealing, 50 Hz		2 VA, Coil in a cold state and 1.0 x Us
Power consumption, sealing, 60 Hz		2 VA, Coil in a cold state and 1.0 x Us
Rated control supply voltage (Us) at AC, 50 Hz - min		100 V
Rated control supply voltage (Us) at AC, 50 Hz - max		130 V
Rated control supply voltage (Us) at AC, 60 Hz - min		100 V
Rated control supply voltage (Us) at AC, 60 Hz - max		130 V
Number of contacts (change-over contacts)		0
Number of contacts (normally closed contacts)		1
Number of contacts (normally open contacts)		1
Safe isolation		250 V AC, Between coil and auxiliary contacts, According to EN 61140 250 V AC, Between auxiliary contacts, According to EN 61140
Equipment heat dissipation, current-dependent Pvid		0 W
Heat dissipation capacity Pdis		0 W
Heat dissipation per pole, current-dependent Pvid		0 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.

10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 8.0

Relays (EG000019) / Timer block (EC002060)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Timer block attachment (ecI@ss10.0.1-27-37-13-08 [ACN996011])		
Switching function		Time-delay dropped out
Setting time	s	5 - 100
Number of contacts as normally open contact		1
Number of contacts as normally closed contact		1
Number of contacts as change-over contact		0
Operating principle		Electronic