

EV busbars 3Ph., 9HP, 80A for PLS. CLS. PKN., PFIM, PFHM, PFNM

Powering Business Worldwide™

EVG-16/3PHAS/9MODUL Part no. Article no. 291471

Similar to illustration

Delivery programme

- 1 P - 3 P - 1		
Basic function	Busbar	
Basic function accessories	Busbar for miniature circuit-breaker Busbar for residual-current circuit-breakers Busbar for combined residual-current/power circuit-breaker	
Туре	Three-phase	
Product range	EVG	

Technical data FTIM 6.0

Technical data ETIM 6.0				
Low-voltage industrial components (EG000017) / Phase busbar (EC000215)				
Electric engineering, automation, process control engineering / Low-voltage swit [ACN992008])	ch technology /	Componer	nt for low-voltage switching technology / Phase busbar (ecl@ss8.1-27-37-13-06	
Number of phases			3	
Number of poles			3	
Suitable for number of devices			3	
Pitch dimensions		mm	0	
Cross section		mm²	16	
Length		mm	160.2	
Number of modular spacings			9	
Rated permanent current lu		Α	80	
Type of electric connection			Fork	
Insulated			Yes	
Rated surge voltage		kV	4	
Conditioned rated short-circuit current Iq		kA	25	
Max. rated operation voltage Ue		V	415	
Rated short-time withstand current lcw		kA	0	
Suitable for devices with N-busbar			No	
Suitable for devices with auxiliary switch			No	

Dimensions

