



Fuse-link, high speed, 100 A, AC 500 V, DC 500 V, 200 kA, 24 x 92 mm, aR, UL

Referencia **SEMI-COND FUSE 100A 500V AC**  
 Catalog No. **FWH-100B**

### Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	100
Rated voltage			AC 500 V DC 500 V
Size			24 x 92 mm
Utilization category			aR
Breaking Capacity		kA	200
usable for size/applications			protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters
Standard/Approval			UL
Shape			centre-bolted tags
Standards/Regulations			UL 248
Optional accessories			fuse-holder BH series

### Technical data ETIM 7.0

Aparatos de protección y fusibles (EG000020) / Fusible para baja tensión tipo NH (EC000055)			
Tecnología electrónica, de automatización y de mando de procesos / Instalación eléctricas, equipo / Inserto de fusibles / Inserto de fusibles de baja tensión (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Tamaño de construcción			Otros
Corriente nominal		Ampere	100
Tensión nominal		Volt	500
Tipo de tensión			CA/CC
Capacidad de conmutación nominal/poder de corte		kiloamper	200
Categoría de uso			Otros
Tipo de indicador de estado de fusible			Ninguno

### Additional product information (links)

Product datasheet (pdf)	<a href="http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-b/Bus_Ele_DS_720007_FWH-(35-1600)A.pdf">http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-b/Bus_Ele_DS_720007_FWH-(35-1600)A.pdf</a>
-------------------------	---