



Fuse-link, high speed, 800 A, AC 500 V, 200 kA, 64 x 161 mm, UL

Referencia **BUSS HIGH SPEED FUSE**
Catalog No. **FWH-800A**

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	800
Rated voltage			AC 500 V
Size			64 x 161 mm
Breaking Capacity		kA	200
usable for size/applications			DC common bus, DC drives, power converters/rectifiers and reduced voltage starters
Standard/Approval			UL
Shape			cylindrical with centre-bolted tags
Standards/Regulations			UL 248

Technical data ETIM 7.0

Aparatos de protección y fusibles (EG000020) / Fusible para baja tensión tipo NH (EC000055)			
Tecnología electrónica, de automatización y de mando de procesos / Instalación eléctricas, equipo / Inserto de fusibles / Inserto de fusibles de baja tensión (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Tamaño de construcción			Otros
Corriente nominal		Ampere	800
Tensión nominal		Volt	500
Tipo de tensión			CA
Capacidad de conmutación nominal/poder de corte		kiloamper	200
Categoría de uso			Otros
Tipo de indicador de estado de fusible			Ninguno

Additional product information (links)

Product datasheet (pdf)	http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-b/Bus_Ele_DS_720007_FWH-(35-1600)A.pdf
-------------------------	---