

## General Information

<b>Extended Product Type:</b>	B7-30-10-80
<b>Product ID:</b>	GJL1311001R8100
<b>EAN:</b>	4013614150197
<b>Catalog Description:</b>	B7-30-10-80 Mini Contactor 220-240V 40-450Hz
<b>Long Description:</b>	The B7-30-10 mini contactor is a compact 3 pole contactor with 1 auxiliary contact and screw terminals. They are ideally suited for applications where reliability is a must and space is at a premium. Mini contactors are used in residential buildings, commercial buildings and industrial applications for the control of single or three-phase loads up to 5.5 kW (AC-3) and 20 A / 690 V (AC-1) or switching of control signals. Further features are the silent coil, a switch position indication and the integrated possibility for rail or wall mounting.

## Categories

Products » Low Voltage Products and Systems » Control Products » Contactors » Mini Contactors

## Ordering

<b>EAN:</b>	4013614150197
<b>Minimum Order Quantity:</b>	1 piece
<b>Customs Tariff Number:</b>	85365080

## Dimensions

<b>Product Net Width:</b>	52.5 mm
<b>Product Net Height:</b>	57.5 mm
<b>Product Net Depth:</b>	46.5 mm
<b>Product Net Weight:</b>	0.175 kg

## Container Information

<b>Package Level 1 Units:</b>	10 piece
<b>Package Level 1 Width:</b>	115 mm
<b>Package Level 1 Height:</b>	54 mm
<b>Package Level 1 Length:</b>	280 mm
<b>Package Level 1 Gross Weight:</b>	1.82 kg
<b>Package Level 1 EAN:</b>	4013614416637

## Technical

<b>Number of Poles:</b>	4
<b>Mini Contactor Type:</b>	Mini Contactor
<b>Rated Operational Voltage:</b>	Auxiliary Circuit 12 ... 240 V DC Auxiliary Circuit 12 ... 500 V AC/DC Main Circuit 12 ... 690 V AC/DC Main Circuit 690 V AC
<b>Rated Frequency (f):</b>	Control Circuit 400 Hz Control Circuit 50 Hz Control Circuit 60 Hz Main Circuit 60 Hz Main Circuit 50 Hz Main Circuit DC
<b>Rated Impulse Withstand Voltage (U<sub>imp</sub>):</b>	Auxiliary Circuit 6 kV Main Circuit 6 kV
<b>Rated Insulation Voltage (U<sub>i</sub>):</b>	690 V acc. to UL/CSA 600 V
<b>Number of Main Contacts NC:</b>	0
<b>Number of Main Contacts NO:</b>	3
<b>Rated Operational Current AC-1 (I<sub>e</sub>):</b>	(220 / 240 V) 40 °C 20 A (220 / 240 V) 55 °C 16 A (380 / 440 V) 40 °C 20 A (380 / 440 V) 55 °C 16 A (690 V) 40 °C 6 A (690 V) 55 °C 6 A
<b>Rated Operational Power AC-3 (P<sub>e</sub>):</b>	(220 / 230 / 240 V) 3 kW (400 V) 5.5 kW (400 V) Three Phase 5.5 kW (440 V) 5.5 kW (500 V) 5.5 kW (690 V) 3 kW
<b>Rated Short-time Withstand Current</b>	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 96 A

(I<sub>cw</sub>):

<b>Number of Auxiliary Contacts NC:</b>	0
<b>Number of Auxiliary Contacts NO:</b>	1
<b>Rated Operational Current AC-15 (I<sub>e</sub>):</b>	(120 V) 4 A (220 / 240 V) 4 A (24 V) 4 A (380 / 400 V) 3 A (500 V) 2 A
<b>Rated Operational Current DC-13 (I<sub>e</sub>):</b>	(110 V) 0.7 A (220 / 240 V) 0.4 A (24 V) 2.5 A
<b>Conventional Free-air Thermal Current (I<sub>th</sub>):</b>	Main Circuit 20 A
<b>Rated Control Circuit Voltage (U<sub>c</sub>):</b>	220 ... 240 V AC
<b>Coil Operating Limits:</b>	(acc. to IEC 60947-4-1) for AC supply 0.85 ... 1.1 x U <sub>c</sub> (at θ ≤ 55 °C)
<b>Degree of Protection:</b>	Auxiliary Circuit Terminals IP20 Control Circuit Terminals IP20 Main Circuit Terminals IP20
<b>Mechanical Durability:</b>	10000000 cycle
<b>Minimum Switching Capacity:</b>	17 V 5 mA
<b>Maximum Electrical Switching Frequency:</b>	AC-1 300 cycles per hour AC-15 600 cycles per hour AC-3 600 cycles per hour DC-1 600 cycles per hour DC-13 600 cycles per hour DC-3 600 cycles per hour
<b>Connecting Capacity-Main Circuit:</b>	Flexible with Ferrule 1/2x 1 ... 2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 1/2x 1 ... 2.5 mm <sup>2</sup> Flexible 1/2x 1 ... 2.5 mm <sup>2</sup> Rigid 1/2x 1 ... 4 mm <sup>2</sup>
<b>Connecting Capacity-Auxiliary Circuit:</b>	Flexible with Ferrule 1/2x 1 ... 2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 1/2x 1 ... 2.5 mm <sup>2</sup> Flexible 1/2x 1 ... 2.5 mm <sup>2</sup> Rigid 1/2x 1 ... 4 mm <sup>2</sup>
<b>Connecting Capacity-Control Circuit:</b>	Flexible with Ferrule 1/2x 1 ... 2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 1/2x 1 ... 2.5 mm <sup>2</sup> Flexible 1/2x 1 ... 2.5 mm <sup>2</sup> Rigid 1/2x 1 ... 4 mm <sup>2</sup>
<b>Wire Stripping Length:</b>	Auxiliary Circuit 9 mm Main Circuit 9 mm
<b>Tightening Torque:</b>	Auxiliary Circuit 0.8 ... 1.1 N·m Control Circuit 0.8 ... 1.1 N·m Main Circuit 0.8 ... 1.1 N·m
<b>Mounting on DIN Rail:</b>	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
<b>Power Loss:</b>	at Rated Operating Conditions per Pole 2 W
<b>Standards:</b>	IEC/EN 60947-1 IEC/EN 60947-4-1 IEC/EN 60947-5-1 UL 60947-1 UL 60947-4-1

## Environmental

<b>Ambient Air Temperature:</b>	Operation -25 ... +55 °C Storage -40 ... +80 °C
<b>Maximum Operating Altitude Permissible:</b>	2000 m
<b>Resistance to Shock acc. to IEC 60068-2-27:</b>	11 ms Pulse 15g
<b>Resistance to Vibrations acc. to IEC 60068-2-6:</b>	5g / 5 ... 150 Hz
<b>RoHS Status:</b>	Following EU Directive 2002/95/EC August 18, 2005 and amendment

## Technical UL/CSA

<b>Maximum Operating Voltage UL/CSA:</b>	Main Circuit 600 V AC
<b>Full Load Amps Motor Use:</b>	(240 V AC) Single Phase 10 A (440 ... 480 V AC) Three Phase 7.6 A
<b>Horsepower Rating UL/CSA:</b>	(208 V AC) Three Phase 3 Hp (220 ... 240 V AC) Single Phase 1.5 Hp (220 ... 240 V AC) Three Phase 3 Hp (440 ... 480 V AC) Three Phase 5 Hp

(550 ... 600 V AC) Three Phase 5 Hp

<b>General Use Rating UL/CSA:</b>	(600 V AC) 16 A
<b>Connecting Capacity Main Circuit UL/CSA:</b>	Stranded 1/2x 22 ... 10 AWG
<b>Connecting Capacity Auxiliary Circuit UL/CSA:</b>	Stranded 1/2x 22 ... 10 AWG
<b>Tightening Torque UL/CSA:</b>	Auxiliary Circuit 7 in-lb Control Circuit 7 in-lb Main Circuit 7 in-lb

### Certificates and Declarations (Document Number)

<b>BV Certificate:</b>	1SAA938000-0203
<b>CB Certificate:</b>	1SAA938000-2002
<b>CCC Certificate:</b>	1SAA938001-3804
<b>cUL Certificate:</b>	1SAA938003-1701
<b>Declaration of Conformity - CE:</b>	1SAD938510-0001
<b>DNV Certificate:</b>	1SAA938000-0305
<b>EAC Certificate:</b>	1SAA920000-2702
<b>GL Certificate:</b>	1SAA938000-0403
<b>LR Certificate:</b>	1SAA938000-0504
<b>RMRS Certificate:</b>	1SAA938000-0703
<b>RoHS Information:</b>	1SAA938003-4403
<b>UL Certificate:</b>	1SAA938000-1604

### Classifications

<b>Object Classification Code:</b>	Q
<b>eClass:</b>	7.0 27371003
<b>ETIM 4:</b>	EC000066 - Magnet contactor, AC-switching
<b>ETIM 5:</b>	EC000066 - Magnet contactor, AC-switching
<b>UNSPSC:</b>	39121529
<b>E-nummer:</b>	3210014

### Accessories [Show accessory images](#)

15 Products Filter

Identifier	Description	Type	Qty	Unit Of Measure
GJL1201317R0002	CA6-11E Auxiliary Contact	CA6-11E	1	piece
GJL1201317R0003	CA6-11M Auxiliary Contact	CA6-11M	1	piece
GJL1201317R0004	CA6-11N Auxiliary Contact	CA6-11N	1	piece
GJL1201330R0002	CAF6-11E Auxiliary Contact	CAF6-11E	1	piece
GJL1201330R0003	CAF6-11M Auxiliary Contact	CAF6-11M	1	piece
GJL1201330R0004	CAF6-11N Auxiliary Contact	CAF6-11N	1	piece
GJL1201330R0006	CAF6-20E Auxiliary Contact	CAF6-20E	1	piece
GJL1201330R0007	CAF6-20M Auxiliary Contact	CAF6-20M	1	piece
GJL1201330R0008	CAF6-20N Auxiliary Contact	CAF6-20N	1	piece
GJL1201330R0010	CAF6-02E Auxiliary Contact	CAF6-02E	1	piece
GJL1201330R0011	CAF6-02M Auxiliary Contact	CAF6-02M	1	piece
GJL1201330R0012	CAF6-02N Auxiliary Contact	CAF6-02N	1	piece
GJL1201904R0001	BN6 Plunger	BN6	1	piece
GJL1201906R0001	LT6-B Cover Cap	LT6-B	1	piece
GJL1201907R0001	LP6 Connecting Link	LP6	1	piece

