



H series heaters with cable

- Metal (M) or touch-safe plastic (P) cover
- 3x20AWG cable with 500mm length
- Clip fastening system for DIN rail TS35
- Heating element consists of a self-regulating PTC resistor

Model	Dimensions	Heating Power	Rated Voltage	Weight	Approvals
	mm	W	V	Kg	
HWM005	78x28x49	5	110-240 V a.c./d.c.	0.110	CE; cURus;
HWM010	78x28x49	10	110-240 V a.c./d.c.	0.110	CE; cURus;
HWM015	78x28x49	15	110-240 V a.c./d.c.	0.110	CE; cURus;
HWM015X	78x28x49	15	110-240 V a.c./d.c.	0.110	CE;
HWM020	78x28x49	20	110-240 V a.c./d.c.	0.110	CE; cURus;
HWM025	108x28x49	25	110-240 V a.c./d.c.	0.150	CE; cURus;
HWM030	108x28x49	30	110-120 V a.c./d.c.	0.150	CE; cURus;
HWM030X	108x28x49	30	110-240 V a.c./d.c.	0.150	CE;
HWM045	108x61.5x85	45	110-240 V a.c./d.c.	0.400	CE; cURus;
HWM045X	108x61.5x85	45	110-240 V a.c./d.c.	0.400	CE;
HWM060	108x61.5x85	60	110-240 V a.c./d.c.	0.400	CE; cURus;
HWM060X	108x61.5x85	60	110-240 V a.c./d.c.	0.400	CE;
HWM080	158x61.5x85	80	110-240 V a.c./d.c.	0.550	CE; cURus;
HWM100	158x61.5x85	100	110-240 V a.c./d.c.	0.550	CE; cURus;
HWM150	208x61.5x85	150	110-240 V a.c./d.c.	0.750	CE; cURus;
HWMS080X	108x61.5x85	80	110-240 V a.c./d.c.	0.425	CE;
HWMS100X	108x61.5x85	100	110-240 V a.c./d.c.	0.425	CE;
HWMS150X	158x61.5x85	150	110-240 V a.c./d.c.	0.575	CE;
HWP045	108x61.5x85	45	110-240 V a.c./d.c.	0.400	CE; cURus;
HWP060	108x61.5x85	60	110-240 V a.c./d.c.	0.400	CE; cURus;
HWP080	158x61.5x85	80	110-240 V a.c./d.c.	0.550	CE; cURus;
HWP100	158x61.5x85	100	110-240 V a.c./d.c.	0.550	CE; cURus;
HWP150	208x61.5x85	150	110-240 V a.c./d.c.	0.750	CE; cURus;