

PRODUCT-DETAILS

# OT25FT3

## OT25FT3 SWITCH-DISCONNECTOR



### General Information

Extended Product Type	OT25FT3
Product ID	1SCA104884R1001
EAN	6417019390277
Catalog Description	OT25FT3 SWITCH-DISCONNECTOR
Long Description	3-pole, front operated, door mounted switch-diconnector / non-fusible diconnect switch with protected clamp terminals, handle is not included

### Ordering

Minimum Order Quantity	10 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

### Popular Downloads

Data Sheet, Technical Information	1SCC301020C0201
Instructions and Manuals	1SCC301056M0006
Mechanical Drawings	1SCC301438F0001 1SCC301437F0001 OT16-40FT3.igs

## Dimensions

Product Net Width	43 mm
Product Net Height	54 mm
Product Net Depth / Length	52 mm
Product Net Weight	0.1 kg

## Technical

Rated Operational Current AC-21A ( $I_e$ )	(380 ... 415 V) 25 A (500 V) 25 A (690 V) 25 A
Rated Operational Current AC-22A ( $I_e$ )	(380 ... 415 V) 25 A (500 V) 25 A (690 V) 25 A
Rated Operational Current AC-23A ( $I_e$ )	(380 ... 415 V) 20 A (500 V) 20 A (690 V) 11 A
Rated Operational Power AC-23A ( $P_e$ )	(220 ... 240 V) 4 kW (400 ... 415 V) 9 kW (500 V) 9 kW (690 V) 9 kW
Conventional Free-air Thermal Current ( $I_{th}$ )	q = 40 °C 32 A
Conventional Thermal Current ( $I_{the}$ )	Fully Enclosed 32 A
Rated Impulse Withstand Voltage ( $U_{imp}$ )	8 kV
Rated Insulation Voltage ( $U_i$ )	acc. to IEC/EN 60664-1 750 V
Rated Operational Voltage	Main Circuit 750 V
Rated Short-Circuit Making Capacity ( $I_{cm}$ )	(690 V) 0.71 kA
Rated Short-time Withstand Current Low Voltage ( $I_{cw}$ )	for 1 s 0.5 kA
Power Loss	at Rated Operating Conditions per Pole 0.6 W
Pollution Degree	3
Handle Type	Handle and shaft not included
Switches Operating Mechanism	Mechanism on Top of the Switch
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Operating Mode	Front operated
Standards	IEC 60947-3 / UL 508 / CSA C22.2 No. 14
Special Functions	No
Mounting Type	Door mounting
Number of Poles	3
Cable Cross-Section	Cu 0.75...10 mm <sup>2</sup>
Degree of Protection	Front IP20
Terminal Type	Screw Terminals
Tightening Torque	acc. IEC 60947-1 0.8 N·m
Mechanical Durability	20000
Lock Type	No

## Technical UL/CSA

Maximum Operating Voltage UL/CSA	600 V
Horsepower Rating UL/CSA	(110 ... 120 V AC) Single Phase 1.5 Hp (240 V AC) Single Phase 3 Hp (440 ... 480 V AC) Single Phase 7.5 Hp (550 ... 600 V AC) Single Phase 10 Hp (220 ... 240 V AC) Three Phase 7,5 Hp (440 ... 480 V AC) Three Phase 15 Hp (550 ... 600 V AC) Three Phase 20 Hp
Ampere Rating UL/CSA	30 A
Tightening Torque UL/CSA	7 in-lb

## Environmental

RoHS Status	Following EU Directive 2011/65/EU
Environmental Information	1SCC301183D0201

## Certificates and Declarations (Document Number)

Declaration of Conformity - CE	1SCC301166D2703
Environmental Information	1SCC301183D0201
Instructions and Manuals	1SCC301056M0006
RoHS Information	1SCC301183D0202
UL Certificate	cULus certificate OT16-80

## Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	63 mm
Package Level 1 Depth / Length	65 mm
Package Level 1 Height	54 mm
Package Level 1 Gross Weight	0.11 kg
Package Level 1 EAN	6417019390277

## Classifications

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnecter
ETIM 6	EC000216 - Switch disconnecter
ETIM 7	EC000216 - Switch disconnecter
ETIM 8	EC000216 - Switch disconnecter
UNSPSC	39122233
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3601435
E-Number (Sweden)	3170945

---

## Categories

---

Low Voltage Products and Systems → Switches → Switch Disconnectors

