




## PRODUCT-DETAILS

## PS1-3-0-65

PS1-3-0-65 3-phase busbar for 3 MS116 / MS132, Ie=65A



### General Information

|                        |  |
|------------------------|--|
| Extended Product Type: | PS1-3-0-65   |
| Product ID:            | 1SAM201906R1103  |
| EAN:                   | 4013614400698  |
| Catalog Description:   | PS1-3-0-65 3-phase busbar for 3 MS116 / MS132, Ie=65A  |
| Long Description:      | PS1-3-0-65 3-phase busbars ensure a quick and safe connection of 3 MS132 or MS116 manual motor starters without lateral auxiliary contacts and are therefore a cost effective solution. The rated current is 65 A. |
| Display Name:          | PS1-3-0-65   |

### Ordering

|                         |          |
|-------------------------|----------|
| Minimum Order Quantity: | 1 piece  |
| Customs Tariff Number:  | 85369010 |

### Popular Downloads

|   |   |
|---|---|
| <b>Data Sheet, Technical Information:</b> | 1SBC100214C0202                                       |
| <b>Instructions and Manuals:</b>          | 2CDC131011M6802<br>2CDC131034M6801<br>2CDC131022M6802 |
| <b>Instructions and Manuals (Part 3):</b> | 1SBC100214C0202                                       |
| <b>CAD Dimensional Drawing:</b>           | 2CDC001079B0201                                       |
| <b>Dimension Diagram:</b>                 | 1SAM200450F0002                                       |

## Dimensions

|                                    |          |
|------------------------------------|----------|
| <b>Product Net Width:</b>          | 131.5 mm |
| <b>Product Net Height:</b>         | 32.3 mm  |
| <b>Product Net Depth / Length:</b> | 13 mm    |
| <b>Product Net Weight:</b>         | 0.055 kg |

## Technical

|   |  |
|---|--|
| <b>Rated Operational Voltage:</b>                         | 690 V AC<br>250 V DC   |
| <b>Rated Operational Current (I<sub>e</sub>):</b>         | 65 A   |
| <b>Rated Impulse Withstand Voltage (U<sub>imp</sub>):</b> | 6 kV   |
| <b>Number of Poles:</b>                                   | 9P   |
| <b>Degree of Protection:</b>                              | IP20   |
| <b>Pollution Degree:</b>                                  | 3  |
| <b>Standards:</b>   | IEC/EN 60947-1<br>IEC/EN 60947-4-1<br>UL 60947-1<br>UL 60947-4-1 |

## Technical UL/CSA

|  |                       |
|--|-----------------------|
| <b>Maximum Operating Voltage UL/CSA:</b> | Main Circuit 600 V AC |
|--|-----------------------|

## Environmental

|                                 |  |
|---------------------------------|--|
| <b>Ambient Air Temperature:</b> | Operation -25 ... +70 °C<br>Storage -50 ... +80 °C |
|---------------------------------|--|

## Material Compliance

|   |                 |
|---|-----------------|
| <b>Conflict Minerals Reporting Template (CMRT):</b> | 9AKK108467A5658 |
| <b>REACH Declaration:</b>                           | 1SAA963005-4502 |
| <b>RoHS Declaration:</b>                            | 1SAA963006-4501 |

|   |  |
|---|--|
| <b>RoHS Information:</b>                    | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| <b>Toxic Substances Control Act - TSCA:</b> | 2CMT2023-006539  |
| <b>WEEE B2C / B2B:</b>                      | Business To Business   |
| <b>WEEE Category:</b>                       | 5. Small Equipment (No External Dimension More Than 50 cm)             |

## Certificates and Declarations

|  |                  |
|--|------------------|
| <b>cUL Certificate:</b>                  | 1SAA963001-1701  |
| <b>Declaration of Conformity - CE:</b>   | 1SAD101100-3411  |
| <b>Declaration of Conformity - UKCA:</b> | 1SAD201100-3411  |
| <b>UL Certificate:</b>                   | E121190-20000619 |

## Container Information

|  |               |
|--|---------------|
| <b>Package Level 1 Units:</b>          | box 10 piece  |
| <b>Package Level 1 Width:</b>          | 80 mm         |
| <b>Package Level 1 Depth / Length:</b> | 181 mm        |
| <b>Package Level 1 Height:</b>         | 46 mm         |
| <b>Package Level 1 Gross Weight:</b>   | 0.588 kg      |
| <b>Package Level 1 EAN:</b>            | 4013614488078 |
| <b>Package Level 2 EAN:</b>            | 4013614581939 |

## External Classifications and Standards

|  |                         |
|--|-------------------------|
| <b>Object Classification Code:</b>         | W                       |
| <b>ETIM 9:</b>                             | EC000215 - Phase busbar |
| <b>ETIM 10:</b>                            | EC000215 - Phase busbar |
| <b>eClass:</b>                             | V11.0 : 27371306        |
| <b>UNSPSC:</b>                             | 39121117                |
| <b>IDEA Granular Category Code (IGCC):</b> | 4378 >> Phase buss bar  |
| <b>E-Number (Finland):</b>                 | 3705949                 |
| <b>E-Number (Norway):</b>                  | 4364001                 |
| <b>E-Number (Sweden):</b>                  | 3111676                 |

## Where Used (as part of "kit")

| Identifier      | Description  | Qty | Unit Of Measure |
|-----------------|--|-----|-----------------|
| 3BHB043890R0006 | UG KIT: PKZ2/ZM TO MS132 (6.3A); ACCESSORY FOR CIRCUIT BREAKER | 1   | piece           |
| 3BHB043890R0010 | UG KIT: PKZ2/ZM TO MS132 (10A); ACCESSORY FOR CIRCUIT BREAKER  | 1   | piece           |

|                 |   |   |       |
|-----------------|---|---|-------|
| 3BHB043890R0016 | UG KIT: PKZ2/ZM TO MS132 (16A); ACCESSORY FOR CIRCUIT BREAKER | 1 | piece |
| 3BHB043890R0025 | UG KIT: PKZ2/ZM TO MS132 (25A); ACCESSORY FOR CIRCUIT BREAKER | 1 | piece |
| 3BHB043890R0032 | UG KIT: PKZ2/ZM TO MS132 (32A); ACCESSORY FOR CIRCUIT BREAKER | 1 | piece |

---

## Categories

---

Products > Low Voltage Products and Systems > Circuit Breakers > Manual Motor Starters

Products > Low Voltage Products and Systems > Control Products > Manual Motor Starters > Manual Motor Starters

