



---

**PRODUCT-DETAILS**

## PS1-5-0-65

PS1-5-0-65 3-phase busbar for 5 MS116 / MS132, I<sub>e</sub>=65A



---

**General Information**

<b>Extended Product Type:</b>	PS1-5-0-65
<b>Product ID:</b>	1SAM201906R1105
<b>EAN:</b>	4013614400711
<b>Catalog Description:</b>	PS1-5-0-65 3-phase busbar for 5 MS116 / MS132, I <sub>e</sub> =65A
<b>Long Description:</b>	PS1-5-0-65 3-phase busbars ensure a quick and safe connection of 5 MS132 or MS116 manual motor starters without lateral auxiliary contacts and are therefore a cost effective solution. The rated current is 65 A.
<b>Display Name:</b>	PS1-5-0-65

---

**Ordering**

<b>Minimum Order Quantity:</b>	1 piece
<b>Customs Tariff Number:</b>	85369010

---

**Popular Downloads**

<b>Data Sheet, Technical Information:</b>	1SBC100214C0202
<b>Instructions and Manuals:</b>	2CDC131011M6802 2CDC131034M6801 2CDC131022M6802
<b>Instructions and Manuals (Part 3):</b>	1SBC100214C0202
<b>CAD Dimensional Drawing:</b>	2CDC001079B0201
<b>Dimension Diagram:</b>	1SAM200450F0004

## Dimensions

<b>Product Net Width:</b>	221.5 mm
<b>Product Net Height:</b>	32.3 mm
<b>Product Net Depth / Length:</b>	13 mm
<b>Product Net Weight:</b>	0.098 kg

## Technical

<b>Rated Operational Voltage:</b>	690 V AC 250 V DC
<b>Rated Operational Current (I<sub>e</sub>):</b>	65 A
<b>Rated Impulse Withstand Voltage (U<sub>imp</sub>):</b>	6 kV
<b>Degree of Protection:</b>	IP20
<b>Pollution Degree:</b>	3
<b>Standards:</b>	IEC/EN 60947-1 IEC/EN 60947-4-1 UL 60947-1 UL 60947-4-1

## Technical UL/CSA

<b>Maximum Operating Voltage UL/CSA:</b>	Main Circuit 600 V AC
--	-----------------------

## Environmental

<b>Ambient Air Temperature:</b>	Operation -25 ... +70 °C Storage -50 ... +80 °C
---------------------------------	--

## Material Compliance

<b>Conflict Minerals Reporting Template (CMRT):</b>	9AKK108467A5658
<b>REACH Declaration:</b>	1SAA963005-4502
<b>RoHS Declaration:</b>	1SAA963006-4501
<b>RoHS Information:</b>	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

<b>Toxic Substances Control Act - TSCA:</b>	2CMT2023-006539
<b>WEEE B2C / B2B:</b>	Business To Business
<b>WEEE Category:</b>	5. Small Equipment (No External Dimension More Than 50 cm)

## Certificates and Declarations

<b>cUL Certificate:</b>	1SAA963001-1701
<b>Declaration of Conformity - CE:</b>	1SAD101100-3411
<b>Declaration of Conformity - UKCA:</b>	1SAD201100-3411
<b>UL Certificate:</b>	E121190-20000619

## Container Information

<b>Package Level 1 Units:</b>	box 10 piece
<b>Package Level 1 Width:</b>	80 mm
<b>Package Level 1 Depth / Length:</b>	264 mm
<b>Package Level 1 Height:</b>	46 mm
<b>Package Level 1 Gross Weight:</b>	1.03 kg
<b>Package Level 1 EAN:</b>	4013614488092
<b>Package Level 2 EAN:</b>	4013614581953

## External Classifications and Standards

<b>Object Classification Code:</b>	W
<b>ETIM 9:</b>	EC000215 - Phase busbar
<b>ETIM 10:</b>	EC000215 - Phase busbar
<b>eClass:</b>	V11.0 : 27371306
<b>UNSPSC:</b>	39121117
<b>IDEA Granular Category Code (IGCC):</b>	4378 >> Phase buss bar
<b>E-Number (Finland):</b>	3705977
<b>E-Number (Norway):</b>	4364003
<b>E-Number (Sweden):</b>	3111678

## Categories

Products > Low Voltage Products and Systems > Circuit Breakers > Manual Motor Starters

Products > Low Voltage Products and Systems > Control Products > Manual Motor Starters > Manual Motor Starters

