

## General Information

Extended Product Type:	TF96-78
Product ID:	1SAZ911201R1004
EAN:	4013614483011
Catalog Description:	TF96-78 Thermal Overload Relay
Long Description:	The TF96-78 thermal overload relay is an economic electromechanical protection device for the main circuit. It offers reliable and fast protection for motors in the event of overload or phase failure. The device has trip class 10. Further features are the temperature compensation, trip contact (NC), signal contact (NO), automatic- or manual reset selectable, trip-free mechanism, STOP function and a trip indication. The overload relays are connected directly to the block contactors. Single mounting kits are available as accessory.

## Categories

Products » Low Voltage Products and Systems » Control Products » Contactors » Thermal Overload Relays

## Ordering

EAN:	4013614483011
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85364900

## Dimensions

Product Net Width:	69.9 mm
Product Net Height:	106.9 mm
Product Net Depth:	106.3 mm
Product Net Weight:	0.52 kg

## Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	97 mm
Package Level 1 Height:	121 mm
Package Level 1 Length:	97 mm
Package Level 1 Gross Weight:	0.62 kg
Package Level 2 Units:	12 piece
Package Level 2 Width:	280 mm
Package Level 2 Height:	210 mm
Package Level 2 Length:	395 mm
Package Level 2 Gross Weight:	7.826 kg
Package Level 2 EAN:	4013614485459

## Technical

Setting Range:	65 ... 78 A
Rated Operational Voltage:	Auxiliary Circuit 600 V AC/DC Main Circuit 690 V AC Main Circuit 440 V DC
Rated Operational Current ( $I_e$ ):	78 A
Rated Operational Current AC-3 ( $I_e$ ):	78 A
Rated Frequency (f):	Auxiliary Circuit 50 Hz Auxiliary Circuit 60 Hz Auxiliary Circuit DC Main Circuit 50 Hz Main Circuit 60 Hz
Rated Impulse Withstand Voltage ( $U_{imp}$ ):	Auxiliary Circuit 6 kV Main Circuit 8 kV
Rated Insulation Voltage ( $U_i$ ):	690 V
Number of Poles:	3
Number of Auxiliary Contacts NC:	1
Number of Auxiliary Contacts NO:	1
Number of Protected Poles:	3
Conventional Free-air Thermal Current ( $I_{th}$ ):	Auxiliary Circuit NC 6 A Auxiliary Circuit NO 4 A
Rated Operational Current AC-15 ( $I_e$ ):	(120 V) NC 3 A (120 V) NO 0.75 A (240 V) NC 3 A (240 V) NO 0.75 A

	(400 V) NC 0.75 A (400 V) NO 0.75 A (500 V) NC 0.75 A (500 V) NO 0.75 A
<b>Rated Operational Current DC-13 (I<sub>e</sub>):</b>	(125 V) NC 0.55 A (125 V) NO 0.55 A (24 V) NC 1.25 A (24 V) NO 1.25 A (250 V) NC 0.27 A (250 V) NO 0.27 A (500 V) NC 0.15 A (500 V) NO 0.15 A (60 V) NC 0.55 A (60 V) NO 0.55 A
<b>Degree of Protection:</b>	Housing IP20 Main Circuit Terminals IP10
<b>Pollution Degree:</b>	3
<b>Connecting Capacity-Auxiliary Circuit:</b>	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm <sup>2</sup> Flexible 1/2x 0.75 ... 1 mm <sup>2</sup> Flexible 1/2x 1 ... 2.5 mm <sup>2</sup> Rigid 1/2x 0.75 ... 4 mm <sup>2</sup>
<b>Connecting Capacity-Main Circuit:</b>	Flexible with Ferrule 1/2x 6 ... 35 mm <sup>2</sup> Flexible with Ferrule 1x 6 ... 50 mm <sup>2</sup> Flexible with Insulated Ferrule 1/2x 6 ... 16 mm <sup>2</sup> Flexible with Insulated Ferrule 1x 6 ... 50 mm <sup>2</sup> Flexible 1/2x 6 ... 35 mm <sup>2</sup> Flexible 1x 6 ... 50 mm <sup>2</sup> Rigid 1/2x 6 ... 35 mm <sup>2</sup> Rigid 1x 6 ... 50 mm <sup>2</sup>
<b>Tightening Torque:</b>	Auxiliary Circuit 1 ... 1.5 N·m Main Circuit 6.0 ... 9.0 N·m
<b>Wire Stripping Length:</b>	Auxiliary Circuit 9 mm Main Circuit 20 mm
<b>Recommended Screw Driver:</b>	Auxiliary Circuit Pozidriv 2 Main Circuit Hexagon 4
<b>Mounting Position:</b>	Position 1 to 6
<b>Power Loss:</b>	at Rated Operating Conditions per Pole 2.7 ... 3.8 W
<b>Suitable For:</b>	AF80 AF96
<b>Standards:</b>	IEC/EN 60947-1 IEC/EN 60947-4-1 IEC/EN 60947-5-1 UL 60947-1 UL 60947-4-1

## Environmental

<b>Ambient Air Temperature:</b>	Operation -25 ... +60 °C Operation Compensated -25 ... +60 °C Storage -50 ... +80 °C
<b>Ambient Air Temperature Compensation:</b>	Yes
<b>Maximum Operating Altitude Permissible:</b>	2000 m
<b>Resistance to Shock acc. to IEC 60068-2-27:</b>	11 ms Pulse 25g
<b>Resistance to Vibrations acc. to IEC 60068-2-6:</b>	5g / 3 ... 150 Hz
<b>RoHS Status:</b>	Following EU Directive 2002/95/EC August 18, 2005 and amendment

## Technical UL/CSA

<b>Maximum Operating Voltage UL/CSA:</b>	Main Circuit 600 V AC
<b>Ampere Rating UL/CSA:</b>	78 A
<b>Contact Rating UL/CSA:</b>	(NC:) B600 (NC:) Q600 (NO:) Q600 (NO:) D300
<b>Connecting Capacity Main Circuit UL/CSA:</b>	Flexible 1x 8 ... 1 AWG Flexible 2x 8 ... 3 AWG Stranded 1x 8 ... 1 AWG Stranded 2x 8 ... 3 AWG
<b>Connecting Capacity Auxiliary</b>	Flexible 1/2x 18 ... 12 AWG

Circuit UL/CSA: Stranded 1/2x 18 ... 12 AWG

Tightening Torque UL/CSA: Auxiliary Circuit 9 ... 13 in·lb  
Main Circuit 53 ... 80 in·lb

### Certificates and Declarations (Document Number)

ABS Certificate:	1SAA941003-0101
BV Certificate:	1SAA941001-0202
CB Certificate:	1SAA941016-2001
CCC Certificate:	1SAA941013-3801
cUL Certificate:	cUL_E48139
Declaration of Conformity - CE:	1SAD938504-0187
DNV Certificate:	1SAA941004-0301
GOST Certificate:	1SAA941001-2701
LR Certificate:	1SAA941003-0501
RINA Certificate:	RINA_ELE098115XG
RoHS Information:	1SAA941008-4401
UL Certificate:	UL_E48139

### Classifications

Object Classification Code:	F
eClass:	7.0 27371501
ETIM 4:	EC000106 - Thermal overload relay
ETIM 5:	EC000106 - Thermal overload relay
UNSPSC:	39121521

