



# Consolidated

ELECTRONIC WIRE & CABLE

Part # 896, 22 AWG (7 x 30) Stranded Tinned Copper Wire, UL Style 1061 VW-1 80°C 300 Volts, CSA SR PVC FT1, Consolidated Hook Up Wire

## Product Construction

### Conductor:

- 22 AWG (7 x 30) Stranded Tinned Copper Wire
- Stranded Tinned Copper Wire Conductor per ASTM B-33

### Insulation:

- Color coded semi rigid PVC
- Temperature -40°C to +80°C
- Voltage Rating: 300 volts

### Applications:

- Consolidated Stranded Tinned Copper Wire UL Style 1061
- Point to point wiring
- Internal wiring of meters, panels, electrical and electronic equipment

### Industry Approvals:

- UL style 1061
- CSA-SR PVC FT1
- RoHS Compliant
- OSHA acceptable

### Packaging:

- 1000 ft. spools
- 1

[+ more](#)



[Specifications](#) | [Other Information](#) | [Disclaimer](#)

Specifications -

|                                |                                                                                |
|--------------------------------|--------------------------------------------------------------------------------|
| <b>Gauge</b>                   | 22 AWG                                                                         |
| <b>Strands</b>                 | (7 x 30) Tin Copper Wire                                                       |
| <b>Nominal Insulation Wall</b> | .009 in.                                                                       |
| <b>Insulation Type</b>         | PVC                                                                            |
| <b>Nominal O.D.</b>            | 0.050 in.                                                                      |
| <b>Color</b>                   | 0-Black/1-Brown/2-Red/3-Orange/4-Yellow/5-Green/6-Blue/7-Violet/8-Gray/9-White |
| <b>Color Code Chart</b>        | <a href="#">Chart-Hook-Up Wire</a>                                             |
| <b>Insulation Temperature</b>  | -40 to +80 °C                                                                  |

|                       |       |
|-----------------------|-------|
| <b>Voltage Rating</b> | 300 V |
|-----------------------|-------|

|                   |   |
|-------------------|---|
| Other Information | — |
|-------------------|---|

|                  |                                   |
|------------------|-----------------------------------|
| <b>Approvals</b> | CSA SR PVC FT1<br>RoHS<br>UL 1061 |
|------------------|-----------------------------------|

|            |   |
|------------|---|
| Disclaimer | — |
|------------|---|

Terms and Conditions for the Consolidated Electronic Wire and Cable Website:

Consolidated has made a very reasonable effort to ensure the accuracy of this "website" pertaining to the information, specifications and the "search" accuracy. The "website" is subject to errors and omissions. The content is subject to change without notice. This "website" is being constantly updated to correct any errors and omissions, but this does not ensure it is completely accurate. Drawings are for general reference only. Consolidated Electronic Wire & Cable is not liable for any direct, indirect, incidental or consequential damages resulting from the use of the material from this "website".

Consolidated Electronic Wire & Cable - 11044 King St., Franklin Park, Illinois 60131 | Toll Free: 800-621-4278 • Phone: 847-455-8830 • Fax: 847-455-8837 | Email: [info@conwire.com](mailto:info@conwire.com)