




LED, BA 9s green, 12-30VAC/DC, 15mA

**Part no.** A22-LED-G  
**Article no.** 261363  
**Catalog No.** A22-LED-GQ

## Delivery programme

Product range			RMQ-Titan (drilling dimensions 22.5 mm)
Basic function			Accessories
Accessories			General accessories
Basic function accessories			Single chip LED
Single unit/Complete unit			Single unit
			For AC and DC voltage (positive pole connected to X1) protected against polarity reversal integral circuit-breaker up to 1500 V
Type			12 - 30 V AC/DC/15 mA
Lifespan to EN 60064 at $t_a = +25\text{ °C}$	$t_{\text{mean}}$ (AC)	h	100000
<b>Colour</b>			Green
			
Connection to SmartWire-DT			no

## Technical data

### General

Ambient temperature			
Open		°C	-25 - +70
Terminal capacities		mm <sup>2</sup>	
Solid		mm <sup>2</sup>	0.75 - 2.5
Stranded		mm <sup>2</sup>	0.5 - 2.5

### Contacts

Rated impulse withstand voltage	$U_{\text{imp}}$	V AC	6000
Rated insulation voltage	$U_i$	V	500
Overvoltage category/pollution degree			III/3

## Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	70

## Technical data ETIM 6.0

Lamps (EG000028) / Indication- and signalling lamp (EC000399)		
Electric engineering, automation, process control engineering / Lighting installation, device / Light medium / Indication- and signal lamp (ecl@ss8.1-27-11-06-31 [AKE242011])		
Lamp voltage	V	24 - 30
Luminous flux	lm	0
Socket		BA9s
Lamp type		LED
Lamp shape		-
Halogen		No
Krypton		No
Xenon		No
Colour		Green
Colour temperature	K	0

Diameter	mm	0
Total length	mm	0
Suitable for torches		No
Suitable for pointer		Yes
Nominal current	mA	15
Lamp power	W	0,45
Average nominal lifespan	h	100000