



Copper strip, tinned, 630A, 11x21x1mm, black

Part no. CU-BAND11X21X1-BK
Catalog No. 080923

EL-Nummer (Norway) 0001711091

Delivery program

| | | | |
|---------------------------|----------------|-----------------|-----------------------------------------------------------------------------------------------------------------------------|
| Product range | | | General switchboard accessories |
| Accessories | | | Copper band insulated |
| Accessories | | | Copper band insulated |
| Description | | | E-Cu laminated conductor, tin-plated UL approved up to max. 600 V AC Insulating material heat resistant up to +105 °C |
| Rated voltage | U _e | V AC | 1000 |
| Rated voltage | U _e | V DC | 1500 |
| Insulation resistance | | kV/mm | 20 |
| Self-extinguishing | | | to UL 94 V0 |
| Length | | mm | 2000 |
| Rated operational current | I _e | A | 630 |
| Dimensions (W x H x D) | | mm | 11 x 21 x 1 |
| Cross-section | | mm ² | 231 |
| Cu factor | | kg | 4,11 |
| Colour | | | Black, similar to RAL 9005 |

Notes

¹Rated operational current: conform to VDE 0281

²Cross-section: Wiring instructions for devices (e.g. terminal capacity at least ... mm²) are to be strictly observed

³Cu factor: Calculating extra material cost Chapter General

Approvals

| | | | |
|--------------------------------------|--|--|----------------------------------------------|
| Product Standards | | | UL 758; EN 60439-1, -3; CE marking |
| UL File No. | | | E248096 |
| UL Category Control No. | | | AVLV2 |
| CSA File No. | | | UL report applies to both US and Canada |
| CSA Class No. | | | – |
| North America Certification | | | UL listed, certified by UL for use in Canada |
| Conditions of Acceptability | | | max. 105 °C |
| Specially designed for North America | | | No |
| Suitable for | | | Appliance Wiring Material - Component |
| Max. Voltage Rating | | | 600 V AC, 750 V DC |