








For use with	Part no. Article no.	Price See price list	Std. pack	Notes	Information relevant for export to North America 	
Side-mounted handle						
<p>For mounting outside the control panel door. Actuation of a switch with toggle lever using a Bowden cable and mechanical components mounted on the front of the switch. For switch with toggle lever.</p> <p>Caution! Intended exclusively for use outside the scope of validity of the IEC/EN 60947 area.</p>						
Handle, metal, black/red						
	Degree of protection UL/CSA Type 12	NZM2...-NA, NS2...-NA NZM3...-NA, NS3...-NA	NZM-XSHGVR12-NA 107269	1 off 	Lockable in 0-position on handle with up to 3 padlocks, for 1 door of an American style control panel (door plus wide bar beside the door). For each handle 1 additional mechanical unit and 1 Bowden cable is required.	Product Standards UL489; CSA-C22.2 No. 5-09 UL File No. E140305 UL CCN DIHS CSA File No. 236770 CSA Class No. 1437-01 NA Certification UL Listed, CSA certified Degree of Protection IEC: IP66, UL/CSA Type 12
	Degree of protection UL/CSA Type 4X		NZM-XSHGVR4X-NA 107268			
Mechanical unit						
		NZM2...-NA, NS2...-NA	NZM2-XSHM-NA 107266	1 off 	For mounting on the front of a switch with toggle lever, including fixing sundries.	UL/CSA certification not required
		NZM3...-NA, NS3...-NA	NZM3-XSHM-NA 107267			
Bowden cables						
	Nominal length 36" = 91.4 cm	NZM2...-NA, NS2...-NA	NZM-XSHBZ36-NA 107263	1 off 		Product Standards UL489; CSA-C22.2 No. 5-09 UL File No. E140305 UL CCN DIHS CSA File No. 236770 CSA Class No. 1437-01 NA Certification UL Listed, CSA certified
	Nominal length 48" = 121.9 cm	NZM3...-NA, NS3...-NA	NZM-XSHBZ48-NA 107264			
	Nominal length 60" = 152.4 cm		NZM-XSHBZ60-NA 107265			