Silencer

SSM Type Muffler

Code	Screw Thread (Size)	S (mm)
SSM-M5	M5	8
SSM-6	1/8"	12
SSM-8	1/4"	15
SSM-10	3/8"	19
SSM-15	1/2"	23
SSM-20	3/4"	30
SSM-25	1"	36

SS-PDK Type Exhaust Muffling Throttle Valve

Code	Screw Thread (Size)	S (mm)
SS-PDK-6	1/8"	13
SS-PDK-8	1/4"	14
SS-PDK-10	3/8"	17
SS-PDK-15	1/2"	22
SS-PDK-20	3/4"	27
SS-PDK-25	1"	34

PTV Plastic Exhaust Muffling Throttle Valve

Code	Screw Thread (Size)	S (mm)
PTV-6	1/8"	10
PTV-8	1/4"	14
PTV-10	3/8"	17
PTV-15	1/2"	24
PTV-20	3/4"	30
PTV-25	1"	36

SB Type Muffler

Code	Screw Thread (Size)	S (mm)
SB-6	1/8"	11
SB-8	1/4"	14
SB-10	3/8"	17
SB-15	1/2"	22
SB-20	3/4"	27
SB-25	1"	33
SB-32	1-1/4"	43
SB-40	1-1/2"	51
SB-50	2"	60

LM Type Aluminum Muffler

Code	Screw Thread (Size)	S (mm)
LM-1	1/8"	20.5
LM-2	1/4"	20.5
LM-3	3/8"	32
LM-4	1/2"	32
LM-6	3/4"	51
LM-8	1"	51

AM Type Aluminum Muffler

Code	Screw Thread (Size)	S (mm)
AM-6	1/8"	16
AM-8	1/4"	19
AM-10	3/8"	22
AM-15	1/2"	29
AM-20	3/4"	38

PSU Type Plastic Muffler

Code	Screw Thread (Size)	S (mm)
PSU-M5	M5	7
PSU-6	1/8"	13
PSU-8	1/4"	17
PSU-10	3/8"	25
PSU-15	1/2"	25
PSU-20	3/4"	
PSU-25	1"	

PSE Type Plastic Muffler

Code	Screw Thread (Size)	S (mm)
PSE-M5	M5	7
PSE-6	1/8"	13
PSE-8	1/4"	17
PSE-10	3/8"	25
PSE-15	1/2"	25
PSE-20	3/4"	37
PSE-25	1"	48

SU Type Plastic Muffler

Code	Screw Thread (Size)	S (mm)
SU-6	1/8"	16
SU-8	1/4"	20
SU-10	3/8"	24
SU-15	1/2"	24
SU-20	3/4"	48
SU-25	1"	48

Air Gun

AG-B-S AG-A-S AG-B-L AG-A-L DG-10 XAG-B-L HG-8

Tube Cutter

Specifcation

Available Tube	Polyurethane and Nylon
Cutting Outer Dia	3.0~14.0
Material	Polyacetal,Stainless Steel

Polyurethane Tube

PU Tube

Ordering Code

PU 8 × 5 — B — 100M

Model code	Tube dia	Tube dia	Tube color	Tube length
PU Tube	OD	ID		200m/roll:(4mm,6mm) 100m/roll:(above 8mm)

Applications

- Pneumatic system,air tools
- Vacuum
- Automation
- Plant Instrumentation
- Paint supply Lines
- Construction applications
- Motion control devices

Specifcation

Working Medium	Compressed air
Working-Pressure	0~1.0MPa
Service temperature range	-20~80℃
Durometer	95 or 98 A

Feature

The Polyethulene tube excels in water-resistant,rseistance,weathering resistance and low temperature resistance.It is more flexibility and kink resistance,also the price is cheaper,more suitable to service piping with strict temperature rwquirements(compared with our Nylon series'tube).

Specifcation

Model	O.D.(mm)	I.D.(mm)	Thickness(mm)	Length M/Roll	Min.bend radius at 20℃(mm)	Min.burst pressure bar at 20℃(bar)	Max.working pressure at 20℃(bar)
PU 4x2.5	4	2.5	0. 75	200	10	30	10
PU 6x4	6	4	1. 00	200	15	30	10
PU 8x5	8	5	1. 50	100	20	30	10
PU 10x6.5	10	6.5	1. 75	100	30	30	10
PU 12x8	12	8	2. 00	100	35	30	10
PU 16x12	16	12	2. 00	100	65	24	8

■ Above listes are just refered the most basic sizes or styles of our products to you. Note:1/4",5/16",3/8",1/2",3/16" and other special sizes are also available.

Color

Color	Tranaparent	Black	Orange	Blue	Dark blue	Sky blue	Clear blue	Green	Red	Yellow	Grey	Milk white
Code	C	B	O	BU	DB	SB	CB	GN	RD	YW	GY	MW
Supplid	●	●	●	●	◆	◆	◆	◆	◆	◆	◆	◆

● means our standard colours of tubing.normally have enough stocks.
◆ means the colours of tubing can be produced if ordered quantity meets our requested(contact us for details).

PUL Series Polyurethane Spiral Tube

PU Spiral Tube

Ordering Code

PUL 8 × 5 — 7 — O

Model code	Outer dia.	Inner dia.	Length(m)	Tube Color
PUL Spirial Type				

Feature

Coiling Tube is suitable for piping of air guns,air screwdrivers and other air tools. Piping of movable parts can be achieved within ed space without distorting the joints.

Length Spes

2	3	5	7	10	14	20
2m	3m	5m	7m	10m	14m	20m

XCPC Pneumatic